

# Tillage Implements



**BUSH HOG®**

IF IT DOESN'T SAY  
**BUSH HOG®**  
IT JUST WON'T CUT IT™



# TABLE OF CONTENTS



IF IT DOESN'T SAY BUSH HOG®, IT JUST WON'T CUT IT.™

TILLAGE



## TILLAGE IMPLEMENTS

Rotary Tillers .....	3
Compact Implements (Standard-Duty Subsoiler, Layoff Plow, Cultivator) .....	6
Lift Disc Harrows .....	7
Pull Disc Harrows .....	12
All-Purpose Plows .....	14
Heavy-Duty Subsoilers .....	16
Pasture Aerators .....	18



# ROTARY TILLERS

RT  
SERIES

RT60G / RT60GR / RT72G / RT72GR / RT84G / RT84GR / RTX / RTC50G

## RTG Series Features

- Rugged construction
- Heavy-duty gearboxes
- Direct gear drive
- Replaceable skids
- Shielded drivelines

One year machine limited warranty with a 5 year limited warranty on the center and side gearboxes (years 3-5, parts only).



## RTG Series Rotary Tillers

59", 70 ½", and 82 ½" tilling widths for 25-65 PTO HP tractors

Units available in both forward rotation (RTG) and reverse rotation (RTGR) models

## RTX Series Features

- Bush Hog®'s heaviest built tiller
- For the toughest jobs
- For higher HP tractors
- Gear drive
- Heavy duty A-frame hitch
- Heavy duty rotor with larger blades

One year machine limited warranty with a 5 year limited warranty on the center and side gearboxes (years 2-5, parts only).



## RTX Series Rotary Tillers

85" and 92" tilling widths for 60 - 90 PTO HP tractors


# ROTARY TILLER SPECIFICATIONS

SERIES:	RTG/RTGR	RTX
Tilling Width	59", 70 ½", 82 ½"	85", 92"
Tractor PTO HP Requirements	25 – 65	60 – 90
Hitch	ASAE Cat. 1, Standard & Quick Hitch; 82 ½" - ASAE Cat. 1 & 2, Standard & Quick Hitch	ASAE Cat. 1 & 2, Standard & Quick Hitch
Blades	L-Shaped	
Number of Blades	42, 54, 66	54, 60
Rotor Speed	211 RPM/540 PTO	235 RPM/540 PTO
Power to Rotor Transmission	Gear Drive, Single Speed	
Number of Flanges on Rotor	7, 9, 11	9, 10
Tillage Depth*	Adjustable to 7" Maximum with Skid Shoe	10" Maximum
Driveline Protection	Slip Clutch	
Weight Range	673 lb. – 831 lb.	1,094 lb. – 1,149 lb.
Warranty	1-Year Machine Limited; 5-Year Limited on Input and Side Gearboxes	

\*May require additional passes depending upon soil type  
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



**RT60GR**



*Gear drive with oil bath in side gearbox is more durable than a chain drive that will wear and could break.*

## RTC Series Features

- Rugged construction
- Heavy-duty gearboxes
- Direct gear drive
- Replaceable skids
- Shielded drivelines



**RTC Series Compact  
 Rotary Tillers**

One year machine limited warranty with a 5 year limited warranty on the center and side gearboxes (years 3-5, parts only).



## COMPACT TILLER SPECIFICATIONS

MODELS:	RTC50G
Total Width	53"
Working Width	48"
Number of Blades	6 Blades Per Flange
Minimum Tractor HP	15 PTO
Type Hitch	ASAE Cat. 1 / Quick Hitch
Offset	Center Mount
Number of Flanges	5
Rotor Speed	253 RPM/540 PTO
Type of Blades	C-Type
Power to Rotor Transmission	Gear Drive
Tillage Depth	6"
Driveline	Slip Clutch Standard
Approximate Weight	374 lb.
Warranty	1-Year Limited Machine Warranty; 5-Year Limited Gearbox Warranty

# COMPACT TILLAGE IMPLEMENTS

3-POINT SUBSOILER,  
LAYOFF PLOW,  
& CULTIVATOR

SS SERIES / LP SERIES / 1RCV SERIES

## SS1 Standard Duty Subsoiler

The 3-point standard duty subsoiler from Bush Hog® is the right tool for you when breaking up a hardpan developed over years. This subsoiler is available with a single shank equipped with a replaceable tip and is capable of ripping the soil a depth of 19". The beveled edge of the high carbon steel shank, combined with a heat-treated replaceable plow point, allows you to cut through the soil with minimal ground disturbance. Shear pin protection is provided. The SS1 is designed for 25 – 45 HP tractors with Cat. 1 Standard and Quick Hitch.



## LP Layoff Plow

Once a field has been broken and disked, the Bush Hog® LP Layoff Plow is used to make rows where crops are planted. The LP has a single, wide prong with a replaceable tip used to lay off and create a bed where you can plant your crops. After the rows are made, the planting can begin. In addition, the Bush Hog® LP Layoff Plow can be used for digging root type vegetables such as potatoes. The layoff plow is designed for 25 – 45 HP tractors with Cat. 1 Standard and Quick Hitch.



## 1RVC Cultivator

The Bush Hog® 1RVC Cultivator is ideal for aerating, stirring and pulverizing the soil to remove weeds, to prepare the ground before planting, or to loosen the soil after the crop has begun to grow. The 1RVC has 6 shanks with replaceable tips and is designed for 25 – 45 HP tractors with Cat. 1 Standard and Quick Hitch. The 1RVC has mounting holes in place for seed planters made by Covington® or Cole. This feature allows for reduced trips over the field and makes the implement even more valuable to you.



## COMPACT TILLAGE IMPLEMENT SPECIFICATIONS

MODELS:	SS1	LP	1RCV
Description	Subsoiler	Layoff Plow	Cultivator
Hitch	Cat. 1 Standard and Quick Hitch		
Overall width	32 3/8"		57 7/8"
Overall height	50"	38"	41 3/16"
Horsepower	25 – 45		
Weight (lb.)	113 lb.	75 lb.	171 lb.
Shank size	3/4" x 6"	3/4" x 4"	3/8" x 1 3/4"
Number of Shanks	1		6
Cutting Point	1/2" x 2 1/2" x 12"	16" x 4.75mm	1/4" x 2 1/2" x 11"
Colors	Available in Bush Hog Red and Major Tractor Colors		

# LIFT DISC HARROWS

D SERIES

1D60-XX / 1D78-XX / 2D78-XX / 2D96-XX / 3D96-XX / 3D118-XX



1D Series



2D Series



3D Series



Bearing hangers reinforced with gussets



Easy-to-grasp handle for simple gang adjustment



Notched discs for maximum cutting action

## ***D Series Features***

- Square and rectangle tube steel frames and gang tubes
- Adjustable gang angles, front and rear, using an easy-to-grasp handle
- Cat. 1 standard and quick hitch on the 1D and 2D series, along with Cat. 1 and 2 standard and quick hitch on the 3D series
- Variable Blade Spacings Available:
  - 9" front and rear gangs for tough-to-cut "New Ground"
  - 7 ½" front and rear gangs for finer soil finishing
  - 9" front gangs / 7 ½" rear gangs – the best of both worlds
- Self-aligning, sealed ball bearings
- Notched disc blades for maximum cutting action
- 1" square, high carbon steel gang axle on the 1D and 2D series, with a 1 ⅛" square, high carbon steel gang axle used on the 3D series
- Available in Bush Hog Red and major tractor colors
- Optional disc scrapers

## 1D SERIES LIFT DISC HARROW SPECIFICATIONS

MODELS:	1D60-XX		1D78-XX
Hitch	Cat. 1 Std. & Quick Hitch		
Recommended HP	35 HP		
Bearing Hanger	3/8" x 6", Dual 1/2" U-Bolts		
Bearing Type - 2/Gang	Self-Aligning, Sealed Ball Bearings		
Angling Capabilities	0, 7, 14, 21 Degrees (Front & Rear Gangs)		
Frame Tubes	2" Square		
Gang Tubes	3" x 1 1/2"		
Gang Axles	1" Square, High Carbon Steel		
Options	Disc Scrapers		

### GANG INFO - 1D60-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	16"	51.4"	58.2"	12	308 lb.	135 lb.	443 lb.	21.5"
7.5" Front & Rear	16"	61"	67.8"	16	348 lb.	135 lb.	483 lb.	26"
9" Front, 7.5" Rear	16"	61"	67.8"	14	312 lb.	135 lb.	447 lb.	21.5" (F) / 26" (R)
9" Front & Rear	18"	51.4"	58.2"	12	344 lb.	135 lb.	479 lb.	21.5"
7.5" Front & Rear	18"	61"	67.8"	16	395 lb.	135 lb.	530 lb.	26"
9" Front, 7.5" Rear	18"	61"	67.8"	14	339 lb.	135 lb.	474 lb.	21.5" (F) / 26" (R)

### GANG INFO - 1D78-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	16"	69"	75.8"	16	372 lb.	135 lb.	507 lb.	31"
7.5" Front & Rear	16"	76.5"	83.3"	20	312 lb.	135 lb.	447 lb.	34"
9" Front, 7.5" Rear	16"	76.5"	83.3"	18	395 lb.	135 lb.	530 lb.	31" (F) / 34" (R)
9" Front & Rear	18"	69"	75.8"	16	420 lb.	135 lb.	555 lb.	31"
7.5" Front & Rear	18"	76.5"	83.3"	20	468 lb.	135 lb.	603 lb.	34"
9" Front, 7.5" Rear	18"	76.5"	83.3"	18	339 lb.	135 lb.	474 lb.	31" (F) / 34" (R)

## 2D SERIES LIFT DISC HARROW SPECIFICATIONS

MODELS:	2D78-XX	2D96-XX
Hitch	Cat. 1 Std. & Quick Hitch	
Recommended HP	65 HP	
Bearing Hanger	3/8" x 6", Dual 5/8" U-Bolts	
Bearing Type - 2/Gang	Self-Aligning, Sealed Ball Bearings	
Angling Capabilities	0, 7, 14, 21 Degrees (Front & Rear Gangs)	
Frame Tubes	2 ½" Square	
Gang Tubes	3" x 2"	
Gang Axles	1" Square, High Carbon Steel	
Options	Disc Scrapers	

### GANG INFO - 2D78-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	18"	70.8"	77.6"	16	452 lb.	223 lb.	675 lb.	31"
7.5" Front & Rear	18"	78.13"	84.9"	20	477 lb.	223 lb.	700 lb.	34"
9" Front, 7.5" Rear	18"	78.13"	84.9"	18	472 lb.	223 lb.	695 lb.	31" (F) / 34" (R)
9" Front & Rear	20"	70.8"	77.6"	16	504 lb.	223 lb.	727 lb.	31"
7.5" Front & Rear	20"	78.13"	84.9"	20	547 lb.	223 lb.	770 lb.	34"
9" Front, 7.5" Rear	20"	78.13"	84.9"	18	543 lb.	223 lb.	766 lb.	31" (F) / 34" (R)

### GANG INFO - 2D96-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	18"	88.9"	95.7"	20	517 lb.	223 lb.	740 lb.	39.5"
7.5" Front & Rear	18"	91.3"	98.2"	24	580 lb.	223 lb.	803 lb.	41"
9" Front, 7.5" Rear	18"	91.3"	98.2"	22	635 lb.	223 lb.	858 lb.	39.5" (F) / 41" (R)
9" Front & Rear	20"	88.9"	95.7"	20	592 lb.	223 lb.	815 lb.	39.5"
7.5" Front & Rear	20"	91.3"	98.2"	24	648 lb.	223 lb.	871 lb.	41"
9" Front, 7.5" Rear	20"	91.3"	98.2"	22	679 lb.	223 lb.	902 lb.	39.5" (F) / 41" (R)

## 3D SERIES LIFT DISC HARROW SPECIFICATIONS

MODELS:	3D96-XX	3D118-XX
Hitch	Cat. 1 & 2 Std. & Quick Hitch	
Recommended HP	95 HP	
Bearing Hanger	1/2" x 7", Dual 5/8" U-Bolts	
Bearing Type - 2/Gang	Self-Aligning, Sealed Ball Bearings	
Angling Capabilities	0, 7, 14, 21 Degrees (Front Gangs); 7, 14, 21 Degrees (Rear Gangs)	
Frame Tubes	3" Square	
Gang Tubes	4" x 3"	
Gang Axles	1 1/8" Square, High Carbon Steel	
Options	Disc Scrapers	

### GANG INFO - 3D96-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	20"	88.8"	95.7"	20	773 lb.	379 lb.	1,152 lb.	40.25"
7.5" Front & Rear	20"	93.4"	100.3"	24	807 lb.	379 lb.	1,186 lb.	42"
9" Front, 7.5" Rear	20"	93.4"	100.3"	22	794 lb.	379 lb.	1,173 lb.	40.25" (F) / 42" (R)
9" Front & Rear	22"	88.8"	95.7"	20	896 lb.	379 lb.	1,275 lb.	40.25"
7.5" Front & Rear	22"	93.4"	100.3"	24	932 lb.	379 lb.	1,311 lb.	42"
9" Front, 7.5" Rear	22"	93.4"	100.3"	22	920 lb.	379 lb.	1,299 lb.	40.25" (F) / 42" (R)

### GANG INFO - 3D118-XX

Disc Blade Spacing	Disc Blade Size	Cutting Width	Overall Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	20"	107"	113.9"	24	867 lb.	379 lb.	1,246 lb.	49.5"
7.5" Front & Rear	20"	106.8"	113.7"	28	1,052 lb.	379 lb.	1,431 lb.	49.5"
9" Front, 7.5" Rear	20"	106.8"	113.7"	26	976 lb.	379 lb.	1,355 lb.	49.5"
9" Front & Rear	22"	107"	113.9"	24	1,002 lb.	379 lb.	1,381 lb.	49.5"
7.5" Front & Rear	22"	106.8"	113.7"	28	1,100 lb.	379 lb.	1,479 lb.	49.5"
9" Front, 7.5" Rear	22"	106.8"	113.7"	26	1,106 lb.	379 lb.	1,485 lb.	49.5"

# PULL DISC HARROWS

DHP  
SERIES

DHP8 / DHP10 / DHP12



Bush Hog®'s Pull Disc Harrows, the DHP Series, are designed for pulverizing soil, seed bed preparation and general tillage. Solidly built units available in widths of 8', 10' and 12', the DHP line of disc harrows are ideally suited for use by small acreage farmers, food plot managers, ranchers, construction crews and nursery operators.

The DHP Series shares many features available on larger, more expensive models, including front-to-rear leveling, a depth control system, adjustable-gang angles, and streamlined tubular gang hangers.

Multiple blade spacing options are available with your DHP Series Pull Disc harrows. Blade spacings of 7 ½" allow for fine, finish discing needed for seedbed preparation or 9" for breaking up and fracturing "new ground" or a combination of the two. Six multiple blade spacing options for each model are available – 20" or 22" notched discs at each of the following spacing options: 7 ½" front & rear, 9" front and rear, 9" front and 7 ½" rear. High strength 1 ½" square gang axles, combined with tough gang components, and triple lip sealed ball bearings, ensure DHP models are ready for the toughest jobs. Put a Bush Hog® DHP disc harrow to work for you today.

## DHP SERIES PULL DISC HARROW SPECIFICATIONS

MODELS:	DHP8	DHP10	DHP12
Drawbar Required HP	40 – 65 HP	45 – 100 HP	55 – 100 HP
Hitch	Pull-Type with Clevis & Hole for 1 ¼" Pin		
Approx. Weight Load on Each Blade	95 – 114 lb.	84 – 98 lb.	78 – 90 lb.
Number of Bearings	8	12	
Disc Bearing Type	Triple Lip Sealed Ball Bearings		
Angling Capabilities	15, 16.5, 18, 19.5, 21 Degrees (Front Gangs); 12, 13.5, 15, 16.5, 18 Degrees (Rear Gangs)		
Frame Tubes	3" Square		
Construction - Tubing	Slide Mainframe, Mainframe Middle, and Gang Arm - 4" x 3" x 1/4"; Mainframe Front and Rear - 5" x 3" x 1/4"; Hitch Frame - 4" x 4" x 1/4"		
Gang Axles	1 ½" Square, High Carbon Steel		
Front to Rear Leveling System	Manual Crank Adjustment		
Depth Control	Cylinder Stroke Control Spacers		
Hydraulic Cylinder	3 ½" x 8" ASAE Hydraulic Cylinder		
Transport Tires and Wheels	(Two) 9.5Lx15 Tires on 15" x 6" – 5 Bolt Wheels		
Park Jack	Standard		
Options	Disc Scrapers, Dual Wheel Transport Kit		

### GANG INFO - DHP8

Disc Blade Spacing	Notched Disc Blade Size	Cutting Width	Apprx. Transport Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	20"	90.25"	8' 10"	20	792 lb.	1,423 lb.	2,215 lb.	40.25"
7.5" Front & Rear	20"	92.5"	8' 10"	24	864 lb.	1,423 lb.	2,287 lb.	42"
9" Front, 7.5" Rear	20"	92.5"	8' 10"	22	828 lb.	1,423 lb.	2,251 lb.	40.25" (F) / 42" (R)
9" Front & Rear	22"	90.25"	8' 10"	20	856 lb.	1,423 lb.	2,279 lb.	40.25"
7.5" Front & Rear	22"	92.5"	8' 10"	24	976 lb.	1,423 lb.	2,399 lb.	42"
9" Front, 7.5" Rear	22"	92.5"	8' 10"	22	916 lb.	1,423 lb.	2,339 lb.	40.25" (F) / 42" (R)

### GANG INFO - DHP10

Disc Blade Spacing	Notched Disc Blade Size	Cutting Width	Apprx. Transport Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	20"	125"	10' 10"	28	1,124 lb.	1,510 lb.	2,634 lb.	58.5"
7.5" Front & Rear	20"	123.25"	10' 10"	32	1,118 lb.	1,510 lb.	2,698 lb.	57.5"
9" Front, 7.5" Rear	20"	123.25"	10' 10"	30	1,156 lb.	1,510 lb.	2,666 lb.	58.5" (F) / 57.5" (R)
9" Front & Rear	22"	125"	10' 10"	28	1,236 lb.	1,510 lb.	2,746 lb.	58.5"
7.5" Front & Rear	22"	123.25"	10' 10"	32	1,272 lb.	1,510 lb.	2,782 lb.	57.5"
9" Front, 7.5" Rear	22"	123.25"	10' 10"	30	1,254 lb.	1,510 lb.	2,764 lb.	58.5" (F) / 57.5" (R)

### GANG INFO - DHP12

Disc Blade Spacing	Notched Disc Blade Size	Cutting Width	Apprx. Transport Width	No. Disc Blades	Gang Weight	Frame Weight	Total Weight	Axle Length
9" Front & Rear	20"	143.25"	12' 4"	32	1,240 lb.	1,510 lb.	2,750 lb.	67.5"
7.5" Front & Rear	20"	140.5"	12' 4"	36	1,300 lb.	1,510 lb.	2,810 lb.	65"
9" Front, 7.5" Rear	20"	140.5"	12' 4"	34	1,270 lb.	1,510 lb.	2,780 lb.	67.5" (F) / 65" (R)
9" Front & Rear	22"	143.25"	12' 4"	32	1,356 lb.	1,510 lb.	2,866 lb.	67.5"
7.5" Front & Rear	22"	140.5"	12' 4"	36	1,468 lb.	1,510 lb.	2,978 lb.	65"
9" Front, 7.5" Rear	22"	140.5"	12' 4"	34	1,412 lb.	1,510 lb.	2,922 lb.	67.5" (F) / 65" (R)

# ALL-PURPOSE PLOWS

APP  
SERIES

APP48-3 / APP60-5 / APP66-5 / APP66-7 / APP85-7 / APP85-9



## ***A simple tool to do serious work...***

Bush Hog®'s line of All-Purpose Plows help you tackle a wide range of ground breaking tasks. These field cultivators break up, cultivate and aerate the ground in agricultural fields, food plots, gardens or anywhere you need to get something growing. Spring loaded, auto-reset shanks allow you to go where other tools can't... stumps, rocks and other obstacles will not keep you from breaking up “new” ground or reclaiming “old” ground. With 3, 5, 7 and 9-shank models available, Bush Hog® has an All-Purpose Plow to meet your ground breaking needs.

## ALL-PURPOSE PLOW SPECIFICATIONS

MODELS: APP48-3   APP60-5   APP66-5   APP66-7   APP85-7   APP85-9						
Overall Width	49 5/8"	61 5/8"	67 5/8"		85 5/8"	
Maximum Working Width	44"	56"	62"		80"	
Overall Depth	39 3/4"					
Overall Height	40 3/8"					
Weight (lb)	206 lb.	228 lb.	284 lb.	367 lb.	386 lb.	455 lb.
# of Shanks	3	5		7		9
Angle Iron Size	2 1/2" (W) x 2 1/2" (H) x 3/8" (T)					
Hole Spacing	1"					
Hitch	Cat. 1 Standard and Quick Hitch					
Teeth	5/16" x 2" x 10 1/8" 1080 High Carbon 38 - 44 Rockwell C Reversible					
Suggested Min. PTO HP	24 HP	35 HP		49 HP		63 HP

### 3, 5, 7, and 9-Shank Models



Spring loaded, auto-reset shanks protect the implement when obstacles such as rocks, stumps or roots are encountered in rough ground.



Heat treated shanks with replaceable points; points are 1080 high carbon steel hardened to 38 - 44 Rockwell C.



Easily adjustable shank spacing in 1" increments; heavy gauge 2 1/2" x 2 1/2" x 3/8" angle iron frame.

# HEAVY-DUTY SUBSOILERS

HDSS  
SERIES

HDSS1S / HDSS1L / HDSS2S / HDSS2L



The 3-point heavy duty subsoilers from Bush Hog® are the right tool for you when breaking up a hardpan developed over years of heavy use. Compacted soil can hurt you in two ways: plant roots can't penetrate into the lower levels of the soil to tap additional nutrients and, in wet conditions, the excess water can't drain away...both weaken your plants and reduce your yields. The HDSS model subsoilers from Bush Hog® are available in four configurations, single or double shank with either short or long shank, capable of ripping the soil to depths ranging from 19" - 23" depending on the shank length. In certain areas, these subsoilers can be used to install water lines at depths suitable to get below the frost line. The beveled edge of the high carbon steel shank, combined with a heat-treated replaceable plow point, allow you to cut through the soil with minimal ground disturbance; shear pin protection is provided. When you need to go deep... the Bush Hog® HDSS subsoilers get the job done for you. Nothing beats a Bush Hog®!

## HEAVY-DUTY SUBSOILER SPECIFICATIONS

MODELS:	HDSS1S	HDSS1L	HDSS2S	HDSS2L
Description	Subsoiler Heavy Duty; 1 Shank Short		Subsoiler Heavy Duty; 2 Shank Short	
Hitch	Cat. 1 & 2, Quick Hitch			
Overall width	41"		49"	
Overall height	39 ½"	43 ½"	39 ½"	43 ½"
Max Depth	19"	23"	19"	23"
Horsepower	Approximately 35 HP per shank up to 85 HP			
Weight	261 lb.	276 lb.	420 lb.	450 lb.
Shank size	1 ¼" x 9 ⅞" x 26 ⅞" (Long); 1 ¼" x 9 ⅞" x 22 ⅞" (Short)			
Number of Shanks	1		2	
Cutting Point	1" x 2 ½" x 9 ⅜", Replaceable, Welded On			

### 1 or 2 Shank Models Available in Major Tractor Colors



Replaceable Heat-Treated Cutting Tip



1 ¼" wide Shanks



Parking Stands are Standard

# PASTURE AERATORS

PA  
SERIES

PA8 / PA10



The PA series pasture aerators from Bush Hog® are designed for use anywhere soil compaction exists. Available in 8' or 10' models, the PA series units are equipped with twisted shanks that serve both to lift and fracture compacted soil. This dual action design improves the intake of water and nutrients and creates improved soil growing conditions. The PA series aerators are ideal for a wide range of potential users including hay producers, cattlemen, sod farmers and landscapers. Give the PA series aerators a chance to make a difference in your soil's potential today!

**Pasture aerators are available in Bush Hog® red plus major tractor colors, and safety tow chains are included.**



Angled rotor adjustment from 2.5° to 7.5° allows the user to achieve even more soil fracturing as the gangs are offset



Heavy duty bearing hangers support the twisted shank rotors



Built-in weight box to ensure maximum soil penetration (weights not included)

## PASTURE AERATOR SPECIFICATIONS

**MODELS: PA8 | PA10**

MODELS: PA8   PA10	
Tractor Horsepower Requirements	40 - 90 HP
Working Width	86"   116"
Overall Width	97.38"   127.63"
Overall Length	136" in Transportation Position
Overall Height (with tines on the ground)	44 ¼"
Weight (lb) [approximate]	1,950 lb.   2,500 lb.
Max. Ballast in Weight Box (lb.) **(Weight Box Included)** (Weights/Ballast NOT included)	2,200 lb.   2,900 lb.
Number of Tines	24 LH & 24 RH   32 LH & 32 RH
Tine Material	Forged & Heat Treated Through Steel
Tine Hub Spacing	7 ½"
Tine Penetration	Up to 8 ½" Depending on Ground Condition
Frame Construction	4" Square Tubing; All Welded Construction
Main Tongue Beam	4" Square
Rotor/Tine Support Hangers	1" x 7" Heavy Duty Hangers
Rotor Bearings	Heavy Duty Greasable Bearings
Rotor Bearing Protection	.38" x 3 ½" Metal Housing
Rotor Angle Adjustment	2.5°, 5°, 7.5°
Tires & Wheels	9.5L x 15 Tires on 15" - 5 Bolt Wheels
Tine Depth Control	Add Cylinder Donuts to Cylinder Rod (Included)
Hydraulic Cylinder	3 ½" x 8"
Transportation Lock	Manual Cylinder Lock
Rear Axle Pivot	Greasable



IF IT DOESN'T SAY  
**BUSH HOG**®  
IT JUST WON'T CUT IT™

2501 Griffin Avenue, Selma, Alabama 36703

Tel: 800-363-6096 | Fax: 334-874-2701



**BushHog.com**



**CONTENT DISCLAIMER:**

The products and information contained in this literature are subject to change without notice. Bush Hog® reserves the right to improve our products and make changes to specifications, designs, and standard equipment without notice. For additional product information, please visit Bush Hog®'s website or see your dealer for complete details.