

BUSH HOG®



*Performance
You Can
Count
On™*

SNOW BLOWERS

SBSA Single Auger | SBDA Double Auger |
SBPT Pull Type | SBSS Skid Steer



SBSA SINGLE AUGER

Single auger snow blowers from Bush Hog® easily cut through winter's icy grasp. High tensile steel flighting feeds snow to the 5-blade fan. Its tight tolerance to the housing sucks in the snow blowing it out of the chute with as little as 15 HP.



For convenience, snow blowers with a main body height of 25" come with a standard manual chute rotator. On larger blowers where operators may not be able to safely reach a manual rotator as standard equipment, all rotators are optional.

SPECIFICATIONS

| Model | SBSA54 | SBSA60 | SBSA72 | SBSA78 | SBSA87 | SBSA97 |
|---|--|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| Product Description | SINGLE AUGER 54" SNOW BLOWER | SINGLE AUGER 60" SNOW BLOWER | SINGLE AUGER 72" SNOW BLOWER | SINGLE AUGER 78" SNOW BLOWER | SINGLE AUGER 87" SNOW BLOWER | SINGLE AUGER 97" SNOW BLOWER |
| Recommended Tractor HP (Engine) | 15 HP | 20 HP | 35 HP | 50 HP | 60 HP | 75 HP |
| Cutting Width | 54" | 60" | 72" | 78" | 87" | 97" |
| Cutting Edge | 3/8" x 1" | 3/8" x 1" | 3/8" x 1" | 1/2" x 1-1/2" | 1/2" x 2" | 1/2" x 2" |
| Auger Diam. | 14" | 14" | 14" | 15" | 19" | 19" |
| Fan Diam. | 21" | 21" | 21" | 23" | 27" | 27" |
| Chute Diam. | 8" | 8" | 10" | 10" | 12" | 12" |
| Chute Rotation (Man/Hyd) | Std/Opt | Std/Opt | Opt/Opt | Opt/Opt | Opt/Opt | Opt/Opt |
| Chute Deflector (Man/Hyd) | Std/Opt | Std/Opt | Std/Opt | Std/Opt | Std/Opt | Std/Opt |
| Main Body Height | 25" | 25" | 29" | 29" | 36" | 36" |
| Hitch (Standard & Quick Hitch) | CAT. 1 | CAT. 1 | CAT. 1 | CAT. 1 & 2 | CAT. 2 | CAT. 2 |
| Weight (LBS.) | 366 | 396 | 540 | 748 | 1,034 | 1,106 |
| Warranty | 2-YEAR LIMITED MACHINE WARRANTY; 5-YEAR LIMITED GEARBOX WARRANTY | | | | | |

SBPT PULL TYPE

Built To Last.



The pull type models are built with the same durability as our forward-facing models. Rather than having to look over your shoulder to guide the blower around objects, the pull type blower follows the path of your tractor. This action keeps the operator driving away from the blown snow, increasing visibility and creating a better operator experience.



A 3PH pull type snow blower can be equipped with an optional hydraulic scraper. Equipped with corner markers so you always know its position, the scraper allows you to pull snow away from doorways and structures so you don't miss a thing.

SPECIFICATIONS

| Model | SBPT78 | SBPT87 |
|---------------------------------|--|---------------------------|
| Product Description | PULL TYPE 78" SNOW BLOWER | PULL TYPE 87" SNOW BLOWER |
| Recommended Tractor HP (Engine) | 50 HP | 60 HP |
| Cutting Width | 78" | 87" |
| Cutting Edge | BOLT ON 1/2" x 1-1/2" | BOLT ON 1/2" x 2" |
| Auger Diam. | 15" | 19" |
| Fan Diam. | 23" | 27" |
| Chute Diam. | 10" | 12" |
| Chute Rotation (Man/Hyd) | Opt/Opt | Opt/Opt |
| Chute Deflector (Man/Hyd) | Std./Opt. 8" cyl. | Std./Opt. 8" cyl. |
| Main Body Height | 29" | 36" |
| Hitch (Standard & Quick Hitch) | CAT. 1 & 2 | CAT. 2 |
| Weight (LBS.) | 900 | 1,175 |
| Rear Mounted Blade | Optional | Optional |
| Warranty | 2-YEAR LIMITED MACHINE WARRANTY; 5-YEAR LIMITED GEARBOX WARRANTY | |

SBDA DUAL AUGER



Dual auger snow blowers from Bush Hog® work well in both acreage and commercial applications. These snow blowers accommodate an additional auger to help chew down the most stubborn of snow banks.



All dual auger model snow blowers feature skid shoes to help maintain consistent placement of the cutting edge and prevent surface damage.

SPECIFICATIONS

| Model | SBDA108 | SBDA1108A | SBDA1108B |
|---------------------------------|--|----------------|----------------|
| Product Description | DOUBLE AUGER 108" SNOW BLOWER | | |
| RPM/Driveline | 540 /1 3/8" 6 | 1000/1 3/8" 21 | 1000/1 3/4" 20 |
| Recommended Tractor HP (Engine) | UP TO 175 HP | | |
| Cutting Width | 108" | | |
| Cutting Edge | 1/2" x 6" | | |
| Auger Diam. | 19" (x1) 15" (x1) | | |
| Fan Diam. | 32" | | |
| Chute Diam. | 13" | | |
| Chute Rotation | Hydraulic | | |
| Chute Deflector (Man/Hyd) | Std/Opt | | |
| Main Body Height | 43" | | |
| Hitch (Standard & Quick Hitch) | CAT. 2 & 3 | | |
| Weight (LBS.) | 1980 | | |
| Warranty | 2-YEAR LIMITED MACHINE WARRANTY; 5-YEAR LIMITED GEARBOX WARRANTY | | |

FEATURES



3-Point / Quick Attach

All single auger PTO driven models are built for Category 1 or Category 2 type 3-Point Hitch. Dual auger PTO driven models are built for Category 2 or Category 3 type 3-Point Hitch. All models are Quick Attach compatible.



Gear Box

The time-proven Comer gearbox transfers PTO power from the tractor into the driveline of the snow blower, ensuring consistent power input to the auger and fan assemblies.



Five-Blade Fan

All Bush Hog® snow blowers now feature a standard five-blade fan. The five blades not only evacuate high volumes of snow quickly, but also feature tighter tolerance to the housing increasing velocity of the snow exiting the chute.



High Tensile Steel Ribbon Flighting

To deliver even the heaviest wet snow to the awaiting fan, Bush Hog® snow blowers use machine formed, hand welded augers made with high tensile steel ribbon flighting to provide strength and durability for years to come.



Manual Deflector

All Bush Hog® snow blowers come with a manual pin-style deflector allowing a true set it and forget it approach to blowing snow.



Skid Shoes

Bush Hog® snow blowers come equipped with adjustable skid shoes, extending the life of the cutting edge and helping to protect surfaces from damage commonly associated with snow removal.

OPTIONS



Manual Rotator

Manual rotators are standard on SBSA54 and SBSA60 single auger models and can be optionally outfitted on most models where operators can safely reach the adjustment handle.



Hydraulic Deflector

Hydraulic deflectors control the distance and arc of the thrown snow and are an available option on all models.



Hydraulic Rotator

The optional hydraulic rotator is the ideal upgrade for tractors with cabs or for contractors/property managers needing to make frequent adjustments. Hydraulic rotators are standard equipment on SBDA108, SBDA1108A, and SBDA1108B models.



Multi-Hinged Deflector

The optional multi-hinged deflector is available for most models and allows increased precision in where snow is blown, allowing snow to be placed closer to the blower or into a truck to be hauled away.

The hydraulic powered Bush Hog® snow blower provides year round benefits to skid loader owners with universal quick attach couplers.

For optimal performance, hydraulic motors need to be matched to the equipment's minimum GPM rating.



SPECIFICATIONS

| Model | SBSS760 | SBSS761 | SBSS762 | SBSS763 | SBSS764 | SBSS765 |
|---------------------------|--|---------|---------|---------|---------|---------|
| Product Description | SKIDSTEER 76" SNOW BLOWER | | | | | |
| Cutting Width | 76" | | | | | |
| Cutting Edge | 1/2" x 3" | | | | | |
| Auger | 19" | | | | | |
| Tube | 3" Square | | | | | |
| Flighting | 5/16 x 2 1/4 | | | | | |
| Auger Diam. | 19" | | | | | |
| GPM (min) | 14-17 | 18-20 | 20-22 | 23-26 | 27-33 | 33-40 |
| Mounting | Universal Skidsteer Attach | | | | | |
| Chute Rotation | Hydraulic | | | | | |
| Chute Diam. | 11" | | | | | |
| Chute Deflector (Man/Hyd) | Std/Opt | | | | | |
| Main Body Height | 31" | | | | | |
| Fan Diam. | 32" | | | | | |
| Fan Shaft | 2" Diam. | | | | | |
| Weight (LBS.) | 950 | | | | | |
| Warranty | 2-YEAR LIMITED MACHINE WARRANTY; 5-YEAR LIMITED GEARBOX WARRANTY | | | | | |



2501 Griffin Ave.
Selma, Alabama 36703
Tel: 800-363-6096
Fax: 334-874-2701
www.bushhog.com

Bush Hog and  (hog icon) are registered trademarks of Alamo Group Inc. Copyright © 2018